

MODEL UBRIX SLIM-55



Physical properties	
Warranty	3 years
Protection	IP55(outdoor)
Special Protection	Topple & fall down protection
Cooling	Natural cooling
Operating temperature	-30C° to +55C°
Humidity	Max.95%(non-regulating)
Dimensions	850mm x 500mm x 2100mm (LxWxH)
Net Weight	280Kg
Gross Weight	321Kg



PARAMETERS

UBRIX SLIM-55

Technical features				
Charging capacity	Up to 60KW	Up to 120KW	Up to 160KW	Up to 180KW
Input/Output power	400VAC±10%-50/60Hz- 3phase			
Power factor	≥0.98			
Efficiency	>95%			
Measuring accuracy	level 0.5			
Output voltage range	CCS: 250~1000VDC			
Output current range	0-200A	0-250A	0-250A	0-250A
Communication	PLC (between charger & vehicle)Ethernet/4G/OCPP 1.6J(optional)			
User interface	LCD 7 inch Touch Screen /RFID card and APP			
Versatility	EN/IEC 61851-1: 2019, EN/IEC 61851-23: 2014.			
Security design	Over/under voltage protection, overload protection, current leakage protection, grounding protection,lightening surge protection			
DC Plugs	CCS2 Cable 5M *2			
Energy Meter	CE certified or PTB (optional)			
RCD	Type A or Type B(optional)			
Advertising display				
Mainboard	Android based Quad-core			
RAM	2GB			
Storage	8GB, can extend to 32GB			
Video format	MPG,MPG-1,MPG-2,MPG-4,AVI,MP4, TS,MKV,WMV			
Maximum decoding resolution	3480x2160			
Picture format	GIF,JPEG,PNG,BMP			
Audio output	2x10W			
Audio format	MP3,24bit linear PCM7.1			
Other format	PDF/RSS, News/Weather-forecast			
Network	Rj45 interface,Wifi,4G,Option,			
The update way for content	Network remote update, U disk update.			
Display mode	Landscape/Portrait, Full Screen/Any Split Screen			
Program upgrade	Remote upgrade, remote upgrade			
Timer switch	Support any time period			
	Panel Type	55 inch LCD Panel		
	Display area	1209*680mm		
	Display ratio	16:09		
	Backlight type	LED backlight		
	Resolution	3480x2160		
	Display color	16.7M		
	Brightness	3500-cd/m2		
	Contrast	3500:01:00		
Panel parameters	View angle	178°(H) / 178°(V)		
	Response time	6ms		
	Life time	50000 hours		



ACTUAL IMAGE
UBRIX SLIM-55

